



HANGCHA GROUP CO., LTD.

Factory site: 666 Xiangfu Road,
Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755
Fax: +86-571-88926789 88132890

sales@hcforklift.com
www.hcforklift.com



Follow us on
Facebook



Follow us on
YouTube



Follow us on
WeChat



Download "Hangcha
Forklift" App



ISO45001
ISO45001:2018



ISO14001
ISO14001:2015



ISO9001
ISO9001:2015



HANGCHA trucks conform
to the European Safety
Requirements.

2025 VERSION 2/COPYRIGHT 2025/11

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.



X Series Diesel / Gasoline / LPG Counterbalanced Forklift Trucks

with capacities of 4,000 to 5,000kg

The World of Hangcha



X Series

Diesel / Gasoline / LPG
Counterbalanced
Forklift Trucks



Innovation design

The X series is the new series of internal combustion counterbalance forklift truck developed by Hangcha independently, adopting the world advanced technologies based on the original products. Through the comprehensive upgrading of appearance molding, energy conservation, environmental protection, comfort, security and reliability, it will become the world-class forklift truck which can meet your overall demands.

Strong appearance and visual impact

The appearance of full truck is developed under the cooperation with professional industrial design company by adopting the appearance design methods of brand-new concept. The streamlined surface modeling design brings smooth lines, elegant appearance, vigorous and steady surface as well as the outstanding inherence, possessing the powerful visual impact.

The appearance of the truck is small, exquisite and concise. which adopting the newly designed parts with opening mould at large area, the appearance will be more humanized.



The new designed mast increase forward visibility 15%



Legroom ↑ 15%



High pressure common rail electronic-controlled engine provide lower failure rate (Common rail engine)



Fuel consumption ↓ 10% (Common rail engine)



Exhaust emission ↓ 35% (Common rail engine)



Aluminous plate-fin radiator provides stronger structure



Grade-speed ability ↑ 15%



Better cold starting performance (Common rail engine)



Water temp ↓ 10 C, oil temp ↓ 10%



Energy conservation and Environmental protection



The standard engine is the high pressure common rail electronic-controlled engine which adopts high pressure multiple injections technology to ensure the strong power take-off, lower emission and better cold starting performance; saving the 10% of energy consumption.



The whole truck adopts LED lights as shiner and new-type panoramic retroreflector to ensure energy conservation and power saving as well as greatly improve the performance and service life of luminaires at the same time.

The full vehicles all adopt the environmental protection material to reduce environmental hazards.

Maintenance



Newly-developed LCD instrument has more comprehensive functions and more stable performance and entirely displays the full truck running state, trouble diagnosis and other important information, which can make the operator more intuitively and conveniently have a better knowledge of truck state and make the maintenance conveniently.



The enlarged opening angle of hood and increase of left and right hood side plates can provide you with convenient and rapid maintenance mode.



Adoption of new generation integrated electric box makes maintenance and repair convenient, layout becomes more reasonable and with better water-proof performance.



Integral locking pin structure on the baseboard can be opened without tool, which is convenient for daily repair and maintenance.

Easy/
Efficiency/
Economy



Fully improved reliability And security



1. The radiator adopts aluminous plate-fin radiator with better performance and higher structural strength. Independent oil radiator, optimized oil and water heat dissipation channel and double ventilation holes on counterweight can greatly improve cooling efficiency and reliability of overloaded operation and ensure reliable operation of the engine.



2. Anti-slip pedal is convenient to get on/off the truck and also more safe for the driver.




4. Optimized hydraulic breather structure and integrated with return oil filter can prolong the service life of hydraulic pressure system.

3. Overhead guard adopts special-shaped steel tube, which can reinforce the strength and improve sealing of the cab.

Comfort


Reduce the caster angle of instrument stand and adopt the integral hood to greatly increase the space underfoot;
The orthodrome of overhead guard fore leg will expand the driving space;



Optimized air intake and exhaust system of full truck, high-capacity exhaust buffer and high-effect intake buffer will reduce the noise of full truck by 3dB and reduce the vibration by 20%.



The design of steering wheel of small diameter and electro-hydraulic system as well as the car-type double-handle combination switch will greatly improve the driving comfort.



Adopt the new-type of box iron. Increase the inside width of inner mast and the spacing between lifting cylinders. The lowering of instruments in the driving cab will greatly increase the forward visibility; The rear visibility will also be greatly improved through the optimization design of counterweight.



Standard Specification

- / Reminder of maintenance
- / LED working light
- / Hydraulic oil filter
- / Electric Flameout
- / Seat with belt
- / Skidproof pedal
- / Air filter
- / Hydraulic oil dipstick
- / Traction device
- / Mast speed limiting valve
- / Full hydraulic power steering
- / Wide view duplex mast
- / Standard forks
- / Standard overhead guard
- / Rear combination LED light
- / Panoramic rearview mirror
- / Filf folder
- / Adjustable steering column
- / Pre-heating indicator
- / Engine fuel pressure warning
- / Neutral switch
- / Engine hood spring
- / Dipstick
- / Pneumatic tyres
- / Standard load backrest
- / Horn
- / Fuel gauge
- / LCD display
- / Cable parking brake
- / Tilt cylinder self-locking valve
- / Fork carriage mounting class III (IV)
- / Timer
- / Load safety valve
- / Charging indicator
- / Water temperature gauge
- / Reversing buzzer
- / Return oil filter
- / Hand grip
- / Integrated controller
- / Oil-water separator
- / Engine fault warning
- / Rubber pedal
- / 2nd hydraulic function
- / Transmission oil temperature warning

Optional Mast

- / Duplex wide view full free mast
- / Trilex wide view full free mast
- / Special duplex wide view mast
- / Wider fork carriage
- / Special forks

Options

- / Cover of tilt cylinder
- / Dual front wheel
- / Cabin
- / High-positioned exhaust system
- / Customer painting
- / Cabin heater
- / LED rear working light
- / Hood lock
- / Double heat insulating pad and leather cover
- / Net cover of radiator
- / Solid tyre
- / Middle-positioned exhaust system
- / Sparkle arrester
- / Suspension seat
- / Fuel tank lock
- / Speed meter
- / Extinguisher
- / Right rear armrest with horn button
- / Counter weight net
- / Height of overhead guard
- / Dual air filter
- / Milometer
- / Waterproof cover on the guard
- / Toolbox

Optional Attachments

- | | |
|-----------------------|-----------------------|
| / Paper roll clamp | / Sideshifter |
| / Rotating bale clamp | / Rotating forks |
| / Load stabilizer | / Fork extensioner |
| / Multi-drum clamp | / Load release device |
| / Bale clamp | / Carton clamp |
| / Drum clamp | / Push-pull device |
| / Dumping clamp | / Bucket |
| / Crane arm | / Hook |
| / String pole | / Lengthened fork |
| / Weigher system | |

